


AN ACOUSTICAL FINISH CASE STUDY FROM INTERNATIONAL CELLULOSE



PROJECT	Valdosta State University Valdosta, GA Executive & Magnolia Dining Areas
PROJECT MANGER	Victoria Douglas, AIA
DETAILS	5,500 Sq Ft. Total @ 3/4" Custom Icy Blue, Timothy Straw & Yellow 221

Established in 1913, Valdosta State University is one of the major centers for education in South Georgia. The pristine design of its Spanish Mission style architecture is an example of its dedication to the richness of its heritage. Therefore, a project like this required an aesthetically pleasing acoustical finish to sustain the mission style design theme.

First, custom integral colors had to be impeccably matched in three separate sections. International Cellulose Corporation's ability to manufacture custom integral colors made SonaKrete™ the fitting choice for this project.

Second, one can only imagine how distracting a lively academic lunch discussion would have been without the highly reflective ceiling plan being correctly treated. Project Manager Victoria Douglas well understood those challenges and chose SonaKrete™ because it rendered an NRC of .75 at only 3/4". After the application of SonaKrete™, Victoria noted, *“Speech intelligibility is a great deal better...I’m very satisfied. SonaKrete™ definitely performed as advertised.”*

SonaKrete™ is a hand-trowelled, premium finish which eliminates the popcorn look of other sprayed acoustic products. SonaKrete™ also qualifies for LEED credits. It is available in white, arctic white and custom integral colors, offering versatile options that help meet both your aesthetic and acoustic needs. **With SonaKrete™, quiet never looked so good.** Contact ICC at **1-877-790-9367** for samples and complete technical data. Please also pay a visit at **www.sonakrete.com**. Would you like to learn even more? ICC also offers architects an AIA/CES Lunch-N-Learn program on the subject of Spray-Applied Acoustic Finishes.

Other Unique SonaKrete Applications



Riverside Theater
Vero Beach, FL



Bedens Brook Club
Skillman, NJ



Johnson & Johnson University
Providence, RI



American Eagle
Pittsburgh, PA



SonaKrete is manufactured with a minimum of 80% recycled content which makes it ideal for "Sustainable Design" LEED projects.

Section 09 83 00
SonaKrete™ Acoustical Finish
Specification Guide

INTRODUCTION

This specification is designed to enable the design professional or specification writer to select the NRC value that best suits the project's requirements. Please edit the NRC value in section 3.03 Line A.

PART 1 – GENERAL

1.01 Section Includes

- A. SonaKrete™ acoustical finish system.

1.02 Project Scheduling

- A. Clips, hangers, supports, sleeves and other attachments to the substrate are to be placed by other trades prior to the application of acoustical finish.
- B. Ducts, piping, conduit or other suspended equipment shall not be positioned until after the application.

1.03 Submittals

- A. Submit one copy of the manufacturer's ISO 9001:2000 Certification.
- B. Submit 2 copies of the test reports indicating compliance with the following:
 - 1. NRC values per ASTM C-423 conducted by a NVLAP certified testing laboratory:

Inches	125Hz	250Hz	500Hz	1kHz	2kHz	4kHz	NRC
.25"	.01	.07	.39	.69	.83	.87	.50
.375"	.06	.11	.46	.77	.84	.89	.55
.50"	.01	.16	.49	.89	1.03	.97	.65
.75"	.25	.48	.81	.85	.85	.94	.75

- 2. Class 1 Fire Rating per ASTM E-84

- C. Submit one copy of the manufacturer's written certification that the materials contain no asbestos, fiberglass or other man-made mineral fibers.
- D. Applicator's certificate: Manufacturer's approval of applicator.
- E. Submit 2 8"x8" samples from the manufacturer.

1.04 Quality Assurance

- A. The Manufacturer must be ISO 9001:2000 Certified.
- B. The Applicator: Must be approved by International Cellulose in performing work of this Section.
- C. Field samples:
 - 1. Construct one field sample panel, 10'x10', to specified thickness to illustrate texture and color.
 - 2. Prepare the sample using the same tools and techniques to be used for the actual application.
 - 3. Locate the sample where directed.
 - 4. The applicator will inform the project architect when the sample is ready for review.
 - 5. Do not start the actual application until the architect has approved the field sample.

1.05 Delivery, Storage and Handling

- A. Deliver in original, unopened containers bearing name of manufacturer and product identification.

- B. Store materials dry, off ground and under cover.
- C. Protect liquid adhesive, sealers & additives from freezing.

1.06 Project Conditions

- A. The air temperature in the room must be a minimum of 40° F and maintained until the material has cured.
- B. The substrate temperature must be a minimum of 40° F.
- C. The General Contractor to provide ventilation to ensure proper curing.

PART 2 – PRODUCTS

2.01 Acceptable Manufacturers

- A. International Cellulose Corporation
12315 Robin Boulevard
Houston, Texas 77045
877-790-9367
FAX: (713) 433-2029

2.02 Materials

- A. SonaKrete™ Acoustical Finish System
- B. SonaPrep
- C. Water – Potable
- D. Color shall be:
 - White Arctic White
 - Custom Color _____

PART 3 – EXECUTION

3.01 Examination

- A. Examine the substrate surfaces and report unsatisfactory conditions in writing. Do not proceed until unsatisfactory conditions are corrected.
- B. Drywall substrates require a minimum Level 3 finish and are to be sealed with SonaPrep.
- C. Plaster substrates require a brown coat finish and are to be sealed with SonaPrep.
- D. Consult International Cellulose for other substrates.

3.02 Preparation

- A. Provide masking, drop cloths or other satisfactory coverings for materials/ surfaces that are not to receive acoustical finish.
- B. Coordinate the installation of the acoustical finish with work of other trades.

3.03 Application

- E. Install to a thickness to achieve an NRC of _____.
- F. Install the acoustical finish according to the manufacturer's written instructions.
- G. After achieving the required thickness and while still wet, float the material to match the approved field sample.
- H. Cure the material with continuous natural or mechanical ventilation.

3.04 Protection

- A. Protect finished installation under provisions of Division 1.

End of Section



**INTERNATIONAL
CELLULOSE
CORPORATION**

12315 Robin Blvd.
Houston, TX 77045
877-790-9367
713-433-2029 FAX
www.sonakrete.com